



Zaozhuang Yiding Bearing Co., Ltd.



KOYO 46230A tapered roller bearings

Bearing No. 46230A

Size	150x225x70 mm
Bore Diameter	150 mm
Outer Diameter	225 mm
Width	70 mm
d	150 mm
D	225 mm
T	70 mm
C	56 mm
r min.	3 mm
r1 min.	1 mm
da min.	164 mm
Da min	213 mm
ra max.	2,5 mm
rb max.	1 mm
Weight	8,82 Kg
Basic dynamic load rating (C)	377 kN
Basic static load rating (C0)	703 kN
(Grease) Lubrication Speed	1200 r/min
(Oil) Lubrication Speed	1600 r/min
Calculation factor (e)	0,33
Calculation factor (Y0)	1,98
Bearing No.	46230A
r(min)	3
r1(min)	1
Cr	472
C0r	703

46230A Bearing 2D drawings and 3D CAD models



Zaozhuang Yiding Bearing Co., Ltd.

Cu	47.0
Grease lub.	1200
Oil lub.	1600
da(min)	164
Da(min)	219
Sa(min)	7
ra(max)	2.5
rb(max)	1
e	0.33
Y2	2.03
Y3	3.02
Y0	1.98
(Refer.) Mass(kg)	8.82