



Zaozhuang Yiding Bearing Co., Ltd.



31.75 mm x 69,012 mm x 19,583 mm NSK 14125A/14276 tapered roller bearings

Bearing No. 14125A/14276

14125A/14276 Bearing 2D drawings and 3D CAD models

Size	31.75x69.012x19.845 mm
Bore Diameter	31.75 mm
Outer Diameter	69,012 mm
Width	19,845 mm
d	31.75 mm
D	69,012 mm
T	19,845 mm
B	19,583 mm
C	15,875 mm
ra1 max.	1,3 mm
a	15,3 mm
r min.	3,5 mm
r1 min.	1,3 mm
Da	60 mm
db	37,5 mm
ra max.	3,5 mm
da	44 mm
Db	63 mm
Weight	0,354 Kg
Basic dynamic load rating (C)	47 kN
Basic static load rating (C0)	56 kN
(Grease) Lubrication Speed	5600 r/min
(Oil) Lubrication Speed	7500 r/min
Calculation factor (e)	0,38
Calculation factor (Y0)	0,86



Zaozhuang Yiding Bearing Co., Ltd.

LangID	1
ALP23	0
outer r	1.3
ALP22	34
D_	69.012
ALP21	28
SHOG_yobi	14125AR/14276R
RAr	124.211
inner r	3.5
GRS rpm	5600
D_b	63
D_a	60
DE_	58.023
SLR	13.3
Prod_Type3	TRBSR_ID_A
BETA_	1
ALPHA_	14.283
SDM_	50.856
DA1	7.767
DA2	6.939
hidYobi	14125A/14276
Y1	1.6
B_	19.583
Oil rpm	7500
hidTable	ecat_NSTPRI
Y0	0.86
inner ra	3.5
outer rb	1.3
C0	56
CUP	0.135
e	0.38
DA_	7.355



Zaozhuang Yiding Bearing Co., Ltd.

BET21	3
BET22	35
BET23	0
Z_	17
C_	15.875
yobi	14125A/14276
KBRG	3161
CONE	0.219
DI_	43.632